

Weighing on Wheels

TIMOTEX

LEADERS IN MOBILE WEIGHING



Weighing hand pallet truck

HPTW - M

Weighing hand pallet truck HPTW - M

specifications

The weighing hand pallet truck type HPTW-M combines a very accurate weighing system with a high quality pallet truck. With the TIMOTEX HPTW-M you weigh pallets and containers during transport, on the place of handling. You save time while checking incoming and outgoing goods, and during dosing and filling processes, and when doing piece counts. The HPTW-M is developed for industrial applications and is protected against water, dust and shocks. The exchangeable battery module provides over 10 hours continuous use per charge.

Functions

- ♦ Automatic and manual zero correction
- ♦ Gross/net weighing
- ♦ Automatic and manual tare
- ♦ Totalling
- ♦ Code entry, max. 10 digits
- ♦ Numeric key board, entry of alpha-numerical data
- ♦ Piece counting by entry or sampling of piece weights (to be specified in the order)
- ♦ Internal clock
- ♦ Error messages in display
- ♦ Automatic switch-off, 10 minutes after the last pushing of a key (switch-off time programmable)



Specifications

Capacity: 2000 kg

Graduation multi-range:

0 - 200 kg: graduation 0.2 kg

200 - 500 kg: graduation 0.5 kg

500 - 2000 kg: graduation 1.0 kg

Maximum inaccuracy:

0.1% of the applied weight

Protection class:

Load cells and cabling IP 67

Indicator IP 65

Battery life: 8 hours

Battery: 12 Vdc / 1.2 Ah

Charger: 230 Volt / 12 Vdc - 300 mA

Options:

- ♦ Built-in printer for printing weighing data onsite, programmable print lay out
- ♦ RS 232 output for communication with PC
- ♦ Client specific software
- ♦ 2 Relay outputs: potential free electronic switches to activate valves or visual/audio signals
- ♦ Extra battery module for continuous use
- ♦ Stainless steel version
- ♦ Stainless steel forks
- ♦ Steering wheels in polyurethane or nylon
- ♦ Loading wheels in nylon and/or tandem
- ♦ Footbrake
- ♦ Capacity 3000 kg (Graduation 1.0 kg)
- ♦ Fork length from 950 mm to 2000 mm
- ♦ Width over forks 690 mm
- ♦ Other options on demand

For special options the standard dimensions can differ from the above standard specifications.

DIMENSIONS in mm

A Fork length	: 1150
B Fork width	: 170
C Minimum fork height	: 90
D Maximum fork height	: 210
Lifting height	: 120
E Width over forks	: 550
F Height to top indicator	: 1003

FEATURES

Colour	: yellow RAL 1028, epoxy painted
Own weight	: 110 kg
Indicator	: rotating
Steering wheels	: rubber
Loading wheels	: polyurethane, single

